# **Technical information**

## **BC-03 Pure Glass Coating**

For professional use only. This information includes an abstract of the Material Safety Data Sheet.

## **Description**

Protective coating for automotive paint and other painted surfaces supplied in a single use packaging (30ml) in the form of a liquid resin and solvents combination ready to use. A thermally neutral hydrolytic sol-gel reaction occurs upon contact with water or humidity.

#### Manufactured by

Modesta Co. Ltd., 761-8054, 20-3 Higashi Hazemachi, Takamatsushi, Kagawa, Japan

## **Information on ingredients**

The following is an informative list of ingredients in the product: Modified Silicone, Modified Silane, Isopropyl Alcohol, Methanol.

## **Hazards & safety identification**

May cause coughing, dizziness, headache and nausea. May cause dry skin, redness and itching. May cause inflammation and itchiness in contact with eyes. May cause headaches, nausea, vomiting and poisoning if swallowed.

Flammable! Suitable Extinguishing Media: Carbon dioxide, Powder, Dry sand, Foam. Do not use water!

#### **Handling and storage**

Keep container tightly closed. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. When using do not eat, drink or smoke. Do not breathe dust. Do not empty into drains. Wear suitable gloves. In case of insufficient ventilation wear suitable respiratory equipment. Dispose of this material and its container to hazardous or special waste collection point. Keep container tightly closed and at a temperature of 20-24 °C.

## **Physical and chemical properties**

Form: Liquid Color: Colorless

Odor: Specific alcoholic odor pH: does not apply

Freezing point: < 0 °C

Flash point: 14 °C (57.2 °F) closed cup Boiling point: 87 °C (188.6 °F)

## **Packaging**

Maximum volume: 30ml

Packaging material: glass bottle (pharmaceutical grade) with neck with

molded screw threads and a leak proof threaded

type cap

Label type: paper self sticking label (UV coated excl. EU)

## **Transport information**

UN Number: UN 1263 - Paint

Hazard primary / subsidiary: Class 3 - Flammable liquid / not applicable

Packaging group: II. (IATA)

