

# Application instructions

## LPS Leather Protection System

The Modesta Leather Protection System delivers exceptional protection to all leather and leather like surfaces in interiors of motor vehicles. This two component system is the only in the market that protects the precious surfaces from both - penetration by liquids and dirt as well as abrasion.

The Base Protection stops liquids from penetrating into the surface, reduces color transfer and makes cleaning of the surface easier with fewer chemicals required. This ensures longer durability of the surfaces and thus preserves the value of the vehicle.

The Slider Abrasion Protection is a unique top coat designed especially for Modesta's Leather Protection System. It reduces surface friction on exposed parts of interiors (for example seat bolsters). Due to the reduced surface friction the exposed parts will last longer without showing signs of the usual wear and tear.

- 1. Thoroughly clean the surface** Use a good quality leather cleaning system and thoroughly clean the leather until clean. You should only use products specifically recommended for cleaning leather surfaces. Products that include a "finish" to them (for example products with an anti static effect) should be avoided.
- 2. Wash residue away with water** Thoroughly wash away all residue of the cleaning products with pure water. Residue left behind from the cleaning step will interact with the LPS and might produce negative effects (protection failure and similar).
- 3. Wipe and leave to dry completely** Wipe off any water and let the clean leather surface to dry completely before proceeding to LPS application.
- 4. Apply the Base Protection** Apply a sufficient amount of product to a dry Modesta applicator and spread well on the surface. Work in criss cross or circular motions and overlap passes. Make sure to spread out evenly on all leather parts where protection is desired.
- 5. Leave to dry** Leave to dry completely for a minimum of three hours.
- 6. Apply the Slider Abrasion Protection** Apply a sufficient amount of product to a dry Modesta applicator and spread well on the surface. Work in criss cross or circular motions and overlap passes. Make sure to spread out evenly on leather parts that are exposed to abrasion (for example seat bolsters and similar). The Slider will reduce the surface friction and thus abrasion of the leather.
- 7. Leave to rest for at least 24 h** Do not sit on the protected surface during this time.

# Application instructions

## LPS Leather Protection System

### Additional notes

Always ensure that surface is properly cleaned before application. Do not apply to surfaces contaminated with silicone, oil, polymers, teflon, wax and similar. **Test on an inconspicuous place before applying.** Surface should have mild (room) temperature before application. Avoid working in too cold or too hot environments. Apply at well-ventilated place. Surface should be dry.

Do not apply on parts that have been recolored, redyed or otherwise repaired or modified unless you have tested the compatibility of the system used with LPS. LPS is a water based product and should be safe to apply on all common leather repair and leather redye systems and products. Due to the vast number of these systems we however can not guarantee compatibility of the LPS with all of them. If you plan to use LPS on a repaired or redyed part you should avoid using the system's own sealant, if any.

After opening the bottle use the whole volume as soon as possible. Once opened, the curing process inside the bottle is started and the product will spoil quickly! Never use a bottle that has been open for more than 7 days.

Do not combine with other products than those recommended. You may seriously harm the finish of the leather and cause irreparable damage!

Do not use the vehicle 24 hours after the application. Exposure to liquids, chemicals and mechanical contact will negatively affect the functionality of the product during this time!

The product requires up to 1 week to gain its final strength and resistance. During this time, exposure to chemicals and liquids should be avoided.

### Aftercare & maintenance

To ensure the longest possible durability and the optimal performance of the Modesta LPS you should keep the interior generally clean. Never use any harsh chemicals to maintain and clean leather unless absolutely needed. No special maintenance is required.

The use of products like leather creams, waxes, milks and other forms of leather care products should be avoided.

Applicators and other accessories may be reused after a thorough wash with pure water.