

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 11/10/2020 Revision date: 1/8/2024 Supersedes version of: 9/13/2023 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product form	: Mixture
Trade name	: Modesta BC-06 - Heat Resistant Hard Glass Coating for Wheels & Body
UFI	: X0UQ-RYT2-080R-VDQA
Product code	: 00312
Product group	: Trade product

1.2.1. Relevant identified uses

Main use category Industrial/Professional use spec Use of the substance/mixture

- : Professional use
- : For professional use only
- : Automotive and aerospace coatings

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Brands Alliance s.r.o. Ltd Prazska 112
SK 81104 Bratislava
T +421244871700
msds@brandsalliance.eu, www.brandsalliance.eu

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2H225Specific target organ toxicity – Repeated exposure, Category 1H372Hazardous to the aquatic environment – Chronic Hazard,H412Category 3Category 4

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).]
Hazard statements (CLP)	 H225 - Highly flammable liquid and vapour. H372 - Causes damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P260 - Do not breathe mist, vapours. P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P273 - Avoid release to the environment. P280 - Wear eye protection, protective gloves. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P314 - Get medical advice/attention if you feel unwell. P370+P378 - In case of fire: Use alcohol resistant foam to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).]	CAS-No.: 64742-88-7 EC-No.: 265-191-7 EC Index-No.: 649-405-00-X	≥ 75	Asp. Tox. 1, H304 STOT RE 1, H372
Octane substance with national workplace exposure limit(s) (PL)	CAS-No.: 111-65-9 EC-No.: 203-892-1 EC Index-No.: 601-009-00-8	1 – 5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact First-aid measures after ingestion	 Get medical advice/attention if you feel unwell. Remove person to fresh air and keep comfortable for breathing. Rinse skin with water/shower. Take off immediately all contaminated clothing. Rinse eyes with water as a precaution. Call a poison center or a doctor if you feel unwell. 			
4.2. Most important symptoms and effects,	both acute and delayed			
Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	 Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard. None under normal conditions. None under normal conditions. None under normal conditions. 			

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures				
5.1. Extinguishing media	Extinguishing media			
Suitable extinguishing media Unsuitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. : Do not use a heavy water stream.			
5.2. Special hazards arising from the subst	tance or mixture			
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Highly flammable liquid and vapour. No direct explosion hazard. Toxic fumes may be released. 			
5.3. Advice for firefighters				
Firefighting instructions Protection during firefighting	 Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 			

SECTION 6: Accidental release measures				
6.1. Personal precautions, protective equipment and emergency procedures				
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.			
6.1.1. For non-emergency personnel				
Protective equipment	: Wear recommended personal protective equipment.			
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray.			
6.1.2. For emergency responders				
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.			

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions				
Avoid release to the environment.				
6.3. Methods and material for containment and cleaning up				
For containment	 Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible. 			
Methods for cleaning up	 Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. 			
Other information	: Dispose of materials or solid residues at an authorized site.			
6.4. Reference to other sections				
For further information refer to section 13.				
SECTION 7: Handling and storage				
7.1. Precautions for safe handling				
Additional hazards when processed Precautions for safe handling	 Not expected to present a significant hazard under anticipated conditions of normal use. Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. 			
Hygiene measures	 Do not eat, drink or smoke when using this product. Always wash hands after handling the product. 			
7.2. Conditions for safe storage, including	any incompatibilities			
Technical measures Storage conditions	 Ground/bond container and receiving equipment. Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container tightly closed. 			
Incompatible products	: Strong bases. Strong acids. Oxidizing agent.			
Storage temperature Packaging materials	: 22 °C : Store always product in container of same material as original container.			
7.3 Specific and use(s)				

No additional information available

peeine

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection				
Туре	Field of application	Characteristics	Standard	
Safety glasses		With side shields	EN 166	

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection		
Туре	Standard	
	EN ISO 6529, EN ISO 20345	

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Chloroprene rubber (CR)	6 (> 480 minutes)	0,4-0,7		EN 374-2, EN ISO 374, EN ISO 374-1

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection				
Device	Filter type	Condition	Standard	
Air-Purifying Respirator (APR), disposable		Short term exposure		

8.2.2.4. Thermal hazards

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liguid
Colour	Colourless
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 165 °C
Flammability	: Highly flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 20.6 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not miscible. Soluble in organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: 0.8
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour. The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (dermal)	Not classified Not classified Not classified
Octane (111-65-9)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 24.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	> ppm
LC50 Inhalation - Rat (Vapours)	> 24.88 mg/l Source: ECHA

solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)

NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male		
STOT-single exposure : Not classified			
Octane (111-65-9)			
STOT-single exposure	May cause drowsiness or dizziness.		
STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.			
Octane (111-65-9)			
NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained
from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon
numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F
to 428°F).] (64742-88-7)

NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female	
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)	
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.	
Aspiration hazard : Not classified		
Octane (111-65-9)		
Viscosity, kinematic	0.801 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'	

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

cology - general : Harmful to aquatic life with long lasting effects. lazardous to the aquatic environment, short–term : Not classified acute) lazardous to the aquatic environment, long–term : Harmful to aquatic life with long lasting effects.			
Octane (111-65-9)			
LC50 - Fish [1]	2.587 mg/l Source: QSAR, ECHA		
EC50 - Crustacea [1]	0.3 mg/l Test organisms (species): Daphnia magna		
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic fish 0.028 mg/l			
solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)			
LC50 - Fish [1] 0.14 mg/l Source: EPISUITE			
EC50 96h - Algae [1] 0.277 mg/l Source: EPISUITE			
12.2. Persistence and degradability			
Modesta BC-06 - Heat Resistant Hard Glass Coating for Wheels & Body			
Persistence and degradability Not rapidly degradable			
Octane (111-65-9)			
Persistence and degradability	Rapidly degradable		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)			
Persistence and degradability Not rapidly degradable			
12.3. Bioaccumulative potential			
Octane (111-65-9)			
Partition coefficient n-octanol/water (Log Pow)	5.18 Source: HSDB		
solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)			
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID		
12.4. Mobility in soil			
No additional information available			
12.5. Results of PBT and vPvB assessment			
No additional information available			
12.6. Endocrine disrupting properties			
No additional information available			
12.7. Other adverse effects			

No additional information available

SECTION 13: Disposal considerations

 Disposal must be done according to official regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal must be done according to official regulations. Disposal must be done according to official regulations. Flammable vapours may accumulate in the container. Do not re-use empty containers. 18 02 05* - chemicals consisting of or containing dangerous substances 20 01 39 - plastics
20 01 02 - glass

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID number				
UN 2920	UN 2920	UN 2920	UN 2920	UN 2920
14.2. UN proper shipping name				
CORROSIVE LIQUID, FLAMMABLE, N.O.S.	CORROSIVE LIQUID, FLAMMABLE, N.O.S.	CORROSIVE LIQUID, FLAMMABLE, N.O.S.	CORROSIVE LIQUID, FLAMMABLE, N.O.S.	CORROSIVE LIQUID, FLAMMABLE, N.O.S.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	ΙΑΤΑ	ADN	RID
Transport document descr	iption		I	
UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S., 8 (3), (D/E)	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S., 8 (3), II	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S., 3 (8), II	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S., 3 (8), II	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S., 3 (8), II
14.3. Transport hazard c		(- , - (-),	- , - (-))
8 (3)	3 (8)	3 (8)	3 (8)	3 (8)
14.4. Packing group			I	l
Not applicable	II	II	II	II
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
Limited quantities (ADR) Excepted quantities (ADR) Fransport category (ADR) Hazard identification number (Drange plates Funnel restriction code (ADR)		33 2920		
Fransport by sea Special provisions (IMDG) Limited quantities (IMDG) Excepted quantities (IMDG) Packing instructions (IMDG) BC packing instructions (IMDG) Fank instructions (IMDG) Fank special provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG) Properties and observations (IMDG- Properties and observations (IMDG) Properties and observations (IMDG)	: T11 G) : TP2 : F-E : S-C : B) : SW	01 :02 2, TP27 : : : : : : : : : : : : : : : : : : :	nucous membranes.	
PCA Excepted quantities (IAT	(A) : E2			
/8/2024 (Revision date)		EU - en		10

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) CAO max net quantity (IATA) Special provisions (IATA) ERG code (IATA)	: Y340 : 0.5L : 352 : 1L : 363 : 5L : A3, A803 : 3CH
Inland waterway transport Classification code (ADN) Special provisions (ADN) Limited quantities (ADN) Excepted quantities (ADN) Equipment required (ADN) Ventilation (ADN) Number of blue cones/lights (ADN)	: CF1 : 274 : 1 L : E2 : PP, EP, EX, A : VE01 : 1
Rail transport Classification code (RID) Special provisions (RID) Limited quantities (RID) Excepted quantities (RID) Packing instructions (RID) Mixed packing provisions (RID) Portable tank and bulk container instructions (RID) Portable tank and bulk container special provisions (RID) Tank codes for RID tanks (RID) Transport category (RID) Colis express (express parcels) (RID)	: CF1 : 274 : 1L : E2 : P001, IBC02 : MP19 : T11 : TP2, TP27 : L4BH : 2 : CE7

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Modesta BC-06 - Heat Resistant Hard Glass Coating for Wheels & Body ; Octane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Modesta BC-06 - Heat Resistant Hard Glass Coating for Wheels & Body ; Octane ; solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).]	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Modesta BC-06 - Heat Resistant Hard Glass Coating for Wheels & Body ; Octane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Octane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Asp. Tox. 1	Aspiration hazard, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
H225	Highly flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H336	May cause drowsiness or dizziness.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.