

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Trade name	: Modesta BC-09 - Hi-PHPS Coating
UFI	: EXS3-1MJ1-R80X-E797
Product code	: 00299
Product group	: Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category	: Professional use
Industrial/Professional use spec	: For professional use only
Use of the substance/mixture	: Automotive and aerospace coatings

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Modesta Japan Ltd  
1580-1 Tahishimomachi  
JP 761-8075 Takamatsushi, Kagawaken  
Japan  
[www.modesta.co](http://www.modesta.co)

##### Distributor

FB Auto Detailing  
Unit 1 Block D  
Liosban Industrial Estate  
IE H91NRK7 Tuam Rd Galway  
T +353 873272729  
[autodetailing.fb@gmail.com](mailto:autodetailing.fb@gmail.com), <https://www.fbdetailing.ie/>

#### 1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Germ cell mutagenicity, Category 1B	H340
Carcinogenicity, Category 1B	H350
Specific target organ toxicity – Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause cancer. May cause genetic defects. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

: Danger

: Petroleum; solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).]

: H225 - Highly flammable liquid and vapour.

H340 - May cause genetic defects (oral).

H350 - May cause cancer (oral).

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P260 - Do not breathe vapours, mist.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective gloves.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P314 - Get medical advice/attention if you feel unwell.

P370+P378 - In case of fire: Use alcohol resistant foam to extinguish.

P391 - Collect spillage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Petroleum substance with national workplace exposure limit(s) (PL); substance with a Community workplace exposure limit	CAS-No.: 64742-48-9 EC-No.: 265-150-3 EC Index-No.: 649-327-00-6	50 – 75	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).]	CAS-No.: 64742-88-7 EC-No.: 265-191-7 EC Index-No.: 649-405-00-X	10 – 30	Asp. Tox. 1, H304 STOT RE 1, H372
Xylene substance with national workplace exposure limit(s) (DE, GB, NL, PL, SI, SK)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Octane substance with national workplace exposure limit(s) (PL)	CAS-No.: 111-65-9 EC-No.: 203-892-1 EC Index-No.: 601-009-00-8	1 – 5	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,1,1,3,3,3-Hexamethyldisilazane	CAS-No.: 999-97-3 EC-No.: 213-668-5	1 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 3, H412
Naphthalene substance with national workplace exposure limit(s) (DE, NL, PL, SK)	CAS-No.: 91-20-3 EC-No.: 202-049-5 EC Index-No.: 601-052-00-2	0.1 – 0.5	Carc. 2, H351 Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.  
Absorb spillage to prevent material damage.

#### For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat. Store in a well-ventilated place. Keep container tightly closed. Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible products : Strong bases. Strong acids. Oxidizing agent.
- Storage temperature : 22 °C
- Packaging materials : Store always product in container of same material as original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protection equipment

##### Personal protective equipment:

Wear recommended personal protective equipment.

##### Personal protective equipment symbol(s):



#### Eye and face protection

##### Eye protection:

Safety glasses

#### Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses		With side shields	EN 166

#### Skin protection

##### Skin and body protection:

Wear suitable protective clothing

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin and body protection	
Type	Standard
	EN ISO 6529, EN ISO 20345

### Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Chloroprene rubber (CR)	6 (> 480 minutes)	0,4-0,7		EN 374-2, EN ISO 374, EN ISO 374-1

### Respiratory protection

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
Air-Purifying Respirator (APR), disposable		Short term exposure	

### Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 165 °C
Flammability	: Highly flammable liquid and vapour.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 20.6 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not miscible. Soluble in organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: 0.8
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Highly flammable liquid and vapour. The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>Petroleum (64742-48-9)</b>	
LD50 oral rat	> 5000 mg/l Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg Source: IUCLID
<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg Source: ECHA
LD50 oral	3600 mg/kg
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LD50 dermal	1700 mg/kg
LC50 Inhalation - Rat (Vapours)	27.57 mg/l/4h
<b>Octane (111-65-9)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 24.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat [ppm]	> ppm
LC50 Inhalation - Rat (Vapours)	> 24.88 mg/l Source: ECHA
<b>Naphthalene (91-20-3)</b>	
LD50 oral rat	≥ 2000 ku/kg Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Naphthalene (91-20-3)</b>	
LD50 oral	490 mg/kg
LD50 dermal rat	≥
LD50 dermal rabbit	2500 µg/kg Source: ChemIDplus
LD50 dermal	2500 mg/kg
LC50 Inhalation - Rat	> 0.4 mg/l air Animal: rat, Guideline: other:EPA TSCA, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
<b>1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)</b>	
LD50 oral rat	851 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	774 mg/kg
LD50 dermal rabbit	547 – 589 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	547 mg/kg
LC50 Inhalation - Rat (Vapours)	12.3 mg/l/4h
<b>solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: May cause genetic defects (oral).
Carcinogenicity	: May cause cancer (oral).
<b>Xylene (1330-20-7)</b>	
IARC group	3 - Not classifiable
<b>Naphthalene (91-20-3)</b>	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
<b>Naphthalene (91-20-3)</b>	
LOAEL (animal/female, F0/P)	50 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
LOAEL (animal/female, F1)	450 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
NOAEL (animal/female, F0/P)	120 mg/kg bodyweight Animal: rabbit, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)



# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)</b>	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male
STOT-single exposure	: Not classified
<b>Octane (111-65-9)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
<b>Octane (111-65-9)</b>	
NOAEC (inhalation, rat, vapour, 90 days)	24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
<b>Naphthalene (91-20-3)</b>	
LOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
LOAEC (inhalation, rat, vapour, 90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
<b>1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)</b>	
NOAEL (oral, rat, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.64 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)
<b>solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)</b>	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: Not classified
<b>Petroleum (64742-48-9)</b>	
Viscosity, kinematic	< 1 mm <sup>2</sup> /s Temp.: 'other:37.8°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
<b>Octane (111-65-9)</b>	
Viscosity, kinematic	0.801 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)

Viscosity, kinematic	0.9 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
----------------------	---

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

#### Petroleum (64742-48-9)

LC50 - Fish [1]	2200 mg/l Source: IUCLID
-----------------	--------------------------

LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID
------------------------------------	-------------------------

#### Xylene (1330-20-7)

LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
-----------------	---

EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
----------------------	---

ErC50 algae	0.799 mg/l
-------------	------------

LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
-------------------	--

NOEC chronic crustacea	0.407 mg/l
------------------------	------------

#### Octane (111-65-9)

LC50 - Fish [1]	2.587 mg/l Source: QSAR, ECHA
-----------------	-------------------------------

EC50 - Crustacea [1]	0.3 mg/l Test organisms (species): Daphnia magna
----------------------	--

LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
----------------	--

NOEC chronic fish	0.028 mg/l
-------------------	------------

#### Naphthalene (91-20-3)

LC50 - Fish [1]	0.77 mg/l
-----------------	-----------

EC50 - Crustacea [1]	2.16 mg/l Test organisms (species): Daphnia magna
----------------------	---

NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
----------------	---

NOEC chronic fish	≈ 0.37 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
-------------------	---

#### 1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)

LC50 - Fish [1]	88 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
-----------------	--

LC50 - Fish [2]	271 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
-----------------	---

EC50 - Crustacea [1]	80 mg/l Test organisms (species): Daphnia magna
----------------------	---

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)</b>	
EC50 72h - Algae [1]	50 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	19 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	50 mg/l
NOEC chronic fish	0.014 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '73 d'
NOEC chronic algae	2.7 mg/l

**solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)**

LC50 - Fish [1]	0.14 mg/l Source: EPISUITE
EC50 96h - Algae [1]	0.277 mg/l Source: EPISUITE

### 12.2. Persistence and degradability

#### Modesta BC-09 - Hi-PHPS Coating

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Petroleum (64742-48-9)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Xylene (1330-20-7)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### Octane (111-65-9)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

#### Naphthalene (91-20-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

#### 1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

**solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)**

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

### 12.3. Bioaccumulative potential

#### Petroleum (64742-48-9)

Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
---	------------------------

#### Xylene (1330-20-7)

Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB
---	-------------------

#### Octane (111-65-9)

Partition coefficient n-octanol/water (Log Pow)	5.18 Source: HSDB
---	-------------------

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Naphthalene (91-20-3)	
Partition coefficient n-octanol/water (Log Pow)	3.3 Source: HSBD
1,1,1,3,3,3-Hexamethyldisilazane (999-97-3)	
Partition coefficient n-octanol/water (Log Pow)	2.62 Source: National Institute of Technology and Evaluation
<b>solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).] (64742-88-7)</b>	
Partition coefficient n-octanol/water (Log Pow)	3.3 – 6 Source: IUCLID

### 12.4. Mobility in soil

Xylene (1330-20-7)	
Mobility in soil	537 Source: ECHA

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>				
PAINT	PAINT	Paint	PAINT	PAINT
<b>Transport document description</b>				
UN 1263 PAINT, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
II	III	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E2  
Transport category (ADR) : 2  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E

#### Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1, TP29  
Stowage category (IMDG) : A  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.  
MFAG-No : 127

#### Air transport

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provisions (IATA) : A3, A72, A192  
ERG code (IATA) : 3L

#### Inland waterway transport

Classification code (ADN) : F1  
Special provisions (ADN) : 163, 367, 640D, 650  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E2  
Equipment required (ADN) : PP, EX, A

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : F1  
Special provisions (RID) : 163, 367, 640D, 650  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7  
Hazard identification number (RID) : 33

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

#### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
28.	Petroleum	Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.
29.	Petroleum	Substances which are classified as germ cell mutagen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 3 or Appendix 4, respectively.
3(a)	Modesta BC-09 - Hi-PHPS Coating ; Petroleum ; Xylene ; Octane ; 1,1,1,3,3,3-Hexamethyldisilazane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Modesta BC-09 - Hi-PHPS Coating ; Petroleum ; Xylene ; Octane ; 1,1,1,3,3,3-Hexamethyldisilazane ; solvent naphtha (petroleum), medium aliph.; Straight run kerosine; [A complex combination of hydrocarbons obtained from the distillation of crude oil or natural gasoline. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C9 through C12 and boiling in the range of approximately 140°C to 220°C (284°F to 428°F).]	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Modesta BC-09 - Hi-PHPS Coating ; Petroleum ; Octane ; 1,1,1,3,3,3-Hexamethyldisilazane	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Petroleum ; Xylene ; Octane ; 1,1,1,3,3,3-Hexamethyldisilazane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor



# Modesta BC-09 - Hi-PHPS Coating

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects (oral).
H350	May cause cancer (oral).
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.