

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 11/11/2020 Revision date: 1/8/2024 Supersedes version of: 11/28/2023 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Modesta BC-M

UFI : DR26-S0C9-931N-1S7A

Product code : 01180
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

Use of the substance/mixture : Exterior care products - all vehicle types

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Modesta Japan Ltd 1580-1 Tahishimomachi

JP 761-8075 Takamatsushi, Kagawaken

Japan

www.modesta.co

Manufacturer

Distributor

Huntsmiths Autmotive Ltd Unit 8C Boundary Road

Brackley GB

NN13 7ES

Northamptonshire

T +441280703163

info@huntsmiths.co.uk, www.huntsmiths.co.uk

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2

H315
Serious eye damage/eye irritation, Category 2

H319
Skin sensitisation, Category 1

H317
Germ cell mutagenicity, Category 2

H341
Reproductive toxicity, Category 1B

Specific target organ toxicity – Single exposure, Category 2

Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Specific target organ toxicity – Repeated exposure, Category 2 H373 Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Suspected of causing genetic defects. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May cause damage to organs. May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

S07 GHS08

Signal word (CLP)

Contains

: Danger

Contains

: propan-2-ol; isopropyl alcohol; isopropanol; Dibutyltin diacetate
P) : H315 - Causes skin irritation.

Hazard statements (CLP)

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H341 - Suspected of causing genetic defects.
H360 - May damage fertility or the unborn child.

H371 - May cause damage to organs.

H373 - May cause damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapours, mist.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment. P280 - Wear eye protection, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P308+P311 - IF exposed or concerned: Call doctor.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P312 - Call doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isopropanol (Isopropyl alcohol) substance with national workplace exposure limit(s) (DE, GB, PL, SI, SK)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0	30 – 50	Flam. Liq. 1, H224 Eye Irrit. 2, H319 STOT SE 3, H336
2-butoxyethanol; Butyl cellosolve substance with national workplace exposure limit(s) (DE, GB, NL, PL, SI, SK); substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0	1 – 5	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Xylene substance with national workplace exposure limit(s) (DE, GB, NL, PL, SI, SK)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Dibutyltin diacetate	CAS-No.: 1067-33-0 EC-No.: 213-928-8 EC Index-No.: 050-033-00-X	1 – 5	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Repr. 1B, H360 Muta. 2, H341 STOT SE 1, H370 STOT RE 1, H372 Aquatic Chronic 1, H410
Methanol substance with national workplace exposure limit(s) (DE, GB, NL, PL, SI, SK)	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	0.1 – 0.5	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT SE 1, H370
Ethylbenzene substance with national workplace exposure limit(s) (DE, GB, NL, PL, SI, SK)	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4	< 0.1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X	(3 ≤ C < 10) STOT SE 2, H371 (10 ≤ C ≤ 100) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

1/8/2024 (Revision date) GB - en 3/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Symptoms/effects after inhalation : Although no appropriate human or animal health effects data are known to exist, this

material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not

breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams. Stop leak without risks if possible. $\label{eq:control}$

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

1/8/2024 (Revision date) GB - en 4/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed Precautions for safe handling

- : Not expected to present a significant hazard under anticipated conditions of normal use.
- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe

dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid

contact with skin and eyes.

Hygiene measures

Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Store in a well-ventilated place. Keep container tightly closed. Keep in a cool, well-ventilated

place away from heat.

Storage conditions

: Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep container

tightly closed.

Incompatible products

: Strong bases. Strong acids. Oxidizing agent.

Storage temperature

: 22 °C

Packaging materials

: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Isopropanol (Isopropyl alcohol) (67-63-0)		
United Kingdom - Occupational Exposure Limits		
Local name	Propan-2-ol	
WEL TWA (OEL TWA)	999 mg/m³	
	400 ppm	
WEL STEL (OEL STEL)	1250 mg/m³	
	500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
2-butoxyethanol; Butyl cellosolve (111-76-2)		
United Kingdom - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
WEL TWA (OEL TWA)	123 mg/m³	
	25 ppm	
WEL STEL (OEL STEL)	246 mg/m³	
	50 ppm	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-butoxyethanol; Butyl cellosolve (111-76-2)	
United Kingdom - Biological limit values	
Local name	2-Butoxyethanol
BMGV	240 mmol/mol Creatinine Parameter: butoxyacetic acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Xylene (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m³ o-,m-,p- or mixed isomers
	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers
	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Methanol (67-56-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Methanol
WEL TWA (OEL TWA)	266 mg/m³
	200 ppm
WEL STEL (OEL STEL)	333 mg/m³
	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Ethylbenzene (100-41-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene
WEL TWA (OEL TWA)	441 mg/m³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m³
	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):









8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses		With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Туре	Standard
	EN ISO 6529, EN ISO 20345

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Chloroprene rubber (CR)	6 (> 480 minutes)	0,4-0,7		EN 374-2, EN ISO 374, EN ISO 374-1

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory protection			
Device Filter type Condition Standard			
Air-Purifying Respirator (APR), disposable		Short term exposure	

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour · white : Not available Odour Odour threshold : Not available : Not available Melting point Freezing point : Not available : > 100 °C Boiling point Flammability : Non flammable. Lower explosion limit : Not available Upper explosion limit : Not available Flash point : Not available Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available

Solubility : Not miscible. Soluble in organic solvents.

: Not available

Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density : Not available Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

9.2. Other information

Viscosity, kinematic

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation) : Not classified		
Isopropanol (Isopropyl alcohol) (67-63-0)		
5840 mg/l Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
4384 mg/kg		
16400 mg/kg Source: ECHA		
1746 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1322 - 2301		
1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961		
> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)		
220 mg/kg		
2.03 mg/l/4h		
3523 mg/kg Source: ECHA		
12126 mg/kg bodyweight Animal: rabbit, Animal sex: male		
1700 mg/kg		
27.57 mg/l/4h		
1187 – 2769 mg/l Animal: rat		
1400 mg/kg		
300 mg/kg Source: ECHA		
3500 mg/kg Source: ECHA, HSDB		
15400 mg/kg Source: ECHA, ChemIDPLUS		
32 mg/kg		
2320 mg/kg Source: GESTIS		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation: Causes skin irritation.Serious eye damage/irritation: Causes serious eye irritation.Respiratory or skin sensitisation: May cause an allergic skin reaction.Germ cell mutagenicity: Suspected of causing genetic defects.Carcinogenicity: Not classified

	Suspected of causing genetic defects. Not classified	
Isopropanol (Isopropyl alcohol) (67-63-0)		
IARC group	3 - Not classifiable	
2-butoxyethanol; Butyl cellosolve (111-76-2)		
IARC group	3 - Not classifiable	
Xylene (1330-20-7)		
IARC group	3 - Not classifiable	
Ethylbenzene (100-41-4)		
IARC group	2B - Possibly carcinogenic to humans	
	May damage fertility or the unborn child.	
Methanol (67-56-1)		
NOAEL (animal/male, F0/P)	< 1000 mg/kg bodyweight Animal: mouse, Animal sex: male	
Dibutyltin diacetate (1067-33-0)		
NOAEL (animal/male, F0/P)	1.9 – 2.3 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)	
NOAEL (animal/female, F0/P)	1.7 – 2.4 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)	
STOT-single exposure :	May cause damage to organs. May cause drowsiness or dizziness.	
Isopropanol (Isopropyl alcohol) (67-63-0)		
STOT-single exposure	May cause drowsiness or dizziness.	
Methanol (67-56-1)		
Methanol (67-56-1) STOT-single exposure	Causes damage to organs.	
	Causes damage to organs.	
STOT-single exposure	Causes damage to organs. Causes damage to organs.	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure		
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure	Causes damage to organs.	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure :	Causes damage to organs.	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure 2-butoxyethanol; Butyl cellosolve (111-76-2)	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure : 2-butoxyethanol; Butyl cellosolve (111-76-2) NOAEL (dermal, rat/rabbit, 90 days)	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure 2-butoxyethanol; Butyl cellosolve (111-76-2) NOAEL (dermal, rat/rabbit, 90 days) Xylene (1330-20-7)	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure 2-butoxyethanol; Butyl cellosolve (111-76-2) NOAEL (dermal, rat/rabbit, 90 days) Xylene (1330-20-7) LOAEL (oral, rat, 90 days)	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral	
STOT-single exposure Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure : 2-butoxyethanol; Butyl cellosolve (111-76-2) NOAEL (dermal, rat/rabbit, 90 days) Xylene (1330-20-7) LOAEL (oral, rat, 90 days) Ethylbenzene (100-41-4)	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-	
Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure 2-butoxyethanol; Butyl cellosolve (111-76-2) NOAEL (dermal, rat/rabbit, 90 days) Xylene (1330-20-7) LOAEL (oral, rat, 90 days) Ethylbenzene (100-41-4) NOAEL (oral, rat, 90 days)	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	
Dibutyltin diacetate (1067-33-0) STOT-single exposure STOT-repeated exposure 2-butoxyethanol; Butyl cellosolve (111-76-2) NOAEL (dermal, rat/rabbit, 90 days) Xylene (1330-20-7) LOAEL (oral, rat, 90 days) Ethylbenzene (100-41-4) NOAEL (oral, rat, 90 days) STOT-repeated exposure	Causes damage to organs. May cause damage to organs through prolonged or repeated exposure. > 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) 75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

 $\label{thm:local_equation} \mbox{Hazardous to the aquatic environment, short-term}$

(acute)

: Harmful to aquatic life with long lasting effects.

: Not classified

Hazardous to the aquatic environment, long–term (chronic)

,	
Isopropanol (Isopropyl alcohol) (67-63-0)	
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
2-butoxyethanol; Butyl cellosolve (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	911 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1840 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
Methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	1340 mg/l
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 - Crustacea [1]	0.42 mg/l
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
	· ·

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethylbenzene (100-41-4)		
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum	
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC chronic crustacea	0.956 mg/l	
Dibutyltin diacetate (1067-33-0)		
LC50 - Fish [1]	3.1 mg/l Source: ECHA	
EC50 - Crustacea [1]	1.4 mg/l Test organisms (species): Daphnia magna	
ErC50 algae	0.1 mg/l	

12.2. Persistence and degradability

Modesta BC-M		
Persistence and degradability	Not rapidly degradable	
Isopropanol (Isopropyl alcohol) (67-63-0)		
Persistence and degradability	Rapidly degradable	
2-butoxyethanol; Butyl cellosolve (111-76-2)		
Persistence and degradability Rapidly degradable		
Xylene (1330-20-7)		
Persistence and degradability	Not rapidly degradable	
Methanol (67-56-1)		
Persistence and degradability Not rapidly degradable		
Ethylbenzene (100-41-4)		
Persistence and degradability Not rapidly degradable		
Dibutyltin diacetate (1067-33-0)		
Persistence and degradability Not rapidly degradable		

12.3. Bioaccumulative potential

Isopropanol (Isopropyl alcohol) (67-63-0)		
Partition coefficient n-octanol/water (Log Pow)	0.05 Source: ICSC	
2-butoxyethanol; Butyl cellosolve (111-76-2)		
Partition coefficient n-octanol/water (Log Pow) 0.81 Source: ECHA		
Xylene (1330-20-7)		
Partition coefficient n-octanol/water (Log Pow) 3.15 Source: HSDB		
Methanol (67-56-1)		
Partition coefficient n-octanol/water (Log Pow) -0.77 Source: HSDB,ChemIDplus		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethylbenzene (100-41-4)	
Partition coefficient n-octanol/water (Log Pow) 3.15 Source: HSDB	
Dibutyltin diacetate (1067-33-0)	
Partition coefficient n-octanol/water (Log Pow) 3.39 Source: ECHA	

12.4. Mobility in soil

Xylene (1330-20-7)	
Mobility in soil	537 Source: ECHA
Methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shippin	14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard o	14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group	14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Isopropanol (Isopropyl alcohol) ; Xylene ; Methanol ; Ethylbenzene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Modesta BC-M; Isopropanol (Isopropyl alcohol); 2- butoxyethanol; Butyl cellosolve; Xylene; Methanol; Ethylbenzene; Dibutyltin diacetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Modesta BC-M ; Dibutyltin diacetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Isopropanol (Isopropyl alcohol) ; Xylene ; Methanol ; Ethylbenzene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
69.	Methanol	Methanol

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): dibutyltin di(acetate) (1067-33-0)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 1	Flammable liquids, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H224	Extremely flammable liquid and vapour.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H332	Harmful if inhaled.	
H336	May cause drowsiness or dizziness.	
H341	Suspected of causing genetic defects.	
H360	May damage fertility or the unborn child.	
H370	Causes damage to organs.	
H371	May cause damage to organs.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Muta. 2	Germ cell mutagenicity, Category 2	
Repr. 1B	Reproductive toxicity, Category 1B	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 1	Specific target organ toxicity – single exposure, Category 1	
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.